

**Bieber Illumination Group**  
**Ocean Pacific Series**

SPECIFICATIONS:  
 ACORN: STABILIZED UV ACRYLIC# FP4518  
 ACORN HOLDER: HEAVY-DUTY  
 CAST ALUMINUM.  
 ELECTRICAL COMPONENTS:  
 EncapLED, an IP66-rated and  
 and ETL listed LED module,  
 combines optics and heat sink  
 into one configurable unit which  
 give precise light distribution.  
 It achieves 110-120 lm/w efficacy  
 with Universal chips and a dimmable  
 driver. Beside maximizing heat  
 dissipation surface, we also  
 utilize convection-based heat  
 management which creates  
 additional air flow around each chip. **60w. LED included - 4000K**  
 POLE: 12' OVER-ALL HEIGHT INCLUDING DECORATIVE  
 CAST BASE. 4" o.d. ROUND, NON-TAPERED, FLUTED,  
 EXTRUDED ALUMINUM POLE SHAFT(3 gage/.250 wall thickness)  
 WITH A TENON. THE DECORATIVE BASE IS ONE PIECE CAST  
 ALUMINUM, 19" dia. x 48" TALL, WITH A HAND HOLE AND COVER.  
 CUSTOM BOLT CIRCLE TO MOUNT ON EXISTING ANCHOR BOLTS:  
 10" ON CENTER BOLT SQUARE - BOLT TO BOLT PATTERN  
 ANCHOR BOLTS: EXISTING  
 FINISH: THE FINISH IS THERMOSET POLYESTER OVEN-BAKED  
 POWDER COAT: RAL 6028 GREEN

DRAWINGS ARE NOT TO SCALE

**OP fixture on Bellagio 12' pole**  
**60w. LED 277v. - RAL6028**

end view of  
fluted tube.

