

# St. John Nichols fixture

**SPECIFICATIONS:**

**HOUSING:** A COMBINATION OF CAST AND SPUN ALUMINUM.

**ELECTRICAL COMPONENTS:** LED or HID:  
HID BALLASTS ARE CWA/HPF REGULATING AUTO-TRANSFORMERS

100 WATT **PULSE START** 120volts. MULTI-TAP OR 20 WATT LED

THE STARTING TEMPERATURE FOR PULSE START & LED IS -20deg F.

**LENS:** CLEAR, ACRYLIC.

**OPTICS:** **STACKED SPUN AND POLISHED LOUVERS**

TYPE V PATTERN FOR 360 DEG. LIGHTING PATTERN, **INCLUDING AN INTERNAL HOUSE SIDE SHIELD, AS REQUIRED**

**SOCKET:** GLAZED PORCELAIN WITH 600v NICKEL COATED CONTACTS. MEDIUM BASE.

**POLE:** **160" x 8" o.d.** ROUND STRAIGHT ALUMINUM, WITH (4) 3/4" DECORATIVE FLAT BARS, 90 DEG. APART. 180 WALL THICKNESS WITH A (2) PIECE ALUMINUM BASE COVER. INCLUDING A HAND HOLE AND COVER. THE TENON IS RECESSED DOWN INTO THE TOP OF THE POLE SHAFT, ALLOWING THE FIXTURE HEAD TO SIT FLUSH ON TOP OF THE POLE.

S/S ALLEN SCREWS HOLD THE FIXTURE IN PLACE.

**FINISH:** THE FINISH IS THERMOSET POLYESTER OVEN-BAKED **POWDER COAT, IN BLACK**, OR ANY STANDARD ISIS LIGHTING COLOR. CUSTOM COLORS ARE ALSO AVAILABLE. PLEASE CONSULT THE FACTORY FOR OPTIONS

**TO ORDER, PLEASE USE THE FOLLOWING CATALOG #:**

**SJN-10-H2-2-L-5-PL-K-K-DB-P-4F-A-2-12-AB11**

**(HID)**

**SJN-10-20w. LED-2-L-5-PL-K-K-DB-P-4F-A-2-12-AB11**

**(LED)**

**LANDSCAPE ARCHITECTS COMMENTS:**

---



---



---

